


HSK-M-EMV/-PVDF-Ex

Metr./NPT



Materiale
Klemmeindsats
Pakning
O-ring
Tæthedegrad

Forniklet messing
PA / PVDF
NBR / FPM
NBR / FPM
IP 68 – 10 bar / IP69K
i det angivne klemmeområde



Kan også leveres med langt gevind
For godkendelser se side 164


| AG | \varnothing mm | Ex- Generation | GL mm | H mm | \varnothing mm | Best.-Nr. HSK-M-EMV-Ex -20°C – 95°C | Best.-Nr. HSK-M-EMV-Ex -60°C – 105°C | Best.-Nr. HSK-M-EMV-PVDF-Ex -20°C – 130°C |
|------------|---------------------|-------------------|----------|---------|---------------------|---|--|---|
| M 12 x 1,5 | 3 - 6,5 | ATEX | 6,5 | 19 | 14 | 1.616.1200.50 | 1.646.1200.50 | |
| M 12 x 1,5 | 2 - 5 | ATEX | 6,5 | 19 | 14 | 1.616.1200.51 | 1.646.1200.51 | |
| M 16 x 1,5 | 6 - 10 | ATEX | 6 | 22 | 20 | 1.616.1600.50 | 1.646.1600.50 | |
| M 16 x 1,5 | 3 - 7 | ATEX | 6 | 22 | 20 | 1.616.1600.51 | 1.646.1600.51 | |
| M 20 x 1,5 | 10 - 14 | ATEX | 6 | 23 | 24 | 1.616.2000.50 | 1.646.2000.50 | |
| M 20 x 1,5 | 7 - 12 | ATEX | 6 | 23 | 24 | 1.616.2000.51 | 1.646.2000.51 | |
| M 25 x 1,5 | 14 - 18 | ATEX | 7 | 24 | 30 | 1.616.2500.50 | 1.646.2500.50 | |
| M 25 x 1,5 | 10 - 16 | ATEX | 7 | 24 | 30 | 1.616.2500.51 | 1.646.2500.51 | |
| M 32 x 1,5 | 20 - 25 | ATEX | 8 | 31 | 40 | 1.616.3200.50 | 1.646.3200.50 | |
| M 32 x 1,5 | 13 - 20 | ATEX | 8 | 31 | 40 | 1.616.3200.51 | 1.646.3200.51 | |
| M 40 x 1,5 | 22 - 32 | ATEX | 8 | 37 | 50 | 1.616.4000.50 | 1.646.4000.50 | |
| M 40 x 1,5 | 20 - 26 | ATEX | 8 | 37 | 50 | 1.616.4000.51 | 1.646.4000.51 | |
| M 50 x 1,5 | 32 - 38 | ATEX | 9 | 37 | 57 | 1.616.5000.50 | 1.646.5000.50 | |
| M 50 x 1,5 | 25 - 31 | ATEX | 9 | 37 | 57 | 1.616.5000.51 | 1.646.5000.51 | |
| M 63 x 1,5 | 37 - 44 | ATEX | 10 | 38 | 64 / 68 | 1.616.6300.50 | 1.646.6300.50 | |
| M 63 x 1,5 | 29 - 35 | ATEX | 10 | 38 | 64 / 68 | 1.616.6300.51 | 1.646.6300.51 | |
| 3/8" NPT | 4 - 8 | ATEX | 15 | 21 | 17 / 19 | 1.616.3800.70 | 1.646.3800.70 | 1.666.3800.70 |
| 3/8" NPT | 2 - 6 | ATEX | 15 | 21 | 17 / 19 | 1.616.3800.71 | 1.646.3800.71 | 1.666.3800.71 |
| 1/2" NPT | 6 - 12 | ATEX | 13 | 24 | 22 / 24 | 1.616.1200.70 | 1.646.1200.70 | 1.666.1200.70 |
| 1/2" NPT | 5 - 9 | ATEX | 13 | 24 | 22 / 24 | 1.616.1200.71 | 1.646.1200.71 | 1.666.1200.71 |
| 3/4" NPT | 14 - 18 | ATEX | 13 | 25 | 30 | 1.616.3400.70 | 1.646.3400.70 | 1.666.3400.70 |
| 3/4" NPT | 10 - 16 | ATEX | 13 | 25 | 30 | 1.616.3400.71 | 1.646.3400.71 | 1.666.3400.71 |

➔ Montagevejledning
side 168



HSK-M-EMV/-PVDF-Ex

PG/PG-lang



Materiale
Klemmeindsats
Pakning
O-ring
Tæthedegrad

Forniklet messing
PA / PVDF
NBR / FPM
NBR / FPM
IP 68 – 10 bar / IP69K
i det angivne klemmeområde

RoHS

Kan også leveres med langt gevind
For godkendelser se side 164


| AG | \varnothing mm | Ex- Generation | GL mm | H mm | \varnothing mm | Best.-Nr. HSK-M-EMV-Ex -20 °C – 95 °C | Best.-Nr. HSK-M-EMV-Ex -60 °C – 105 °C | Best.-Nr. HSK-M-EMV-PVDF-Ex -20 °C – 130 °C |
|---------|---------------------|-------------------|----------|---------|---------------------|---|--|---|
| PG 7 | 3 - 6,5 | ATEX | 5 | 19 | 14 | 1.616.0700.01 | 1.646.0700.01 | 1.666.0700.01 |
| PG 7 | 2 - 5 | ATEX | 5 | 19 | 14 | 1.616.0700.15 | 1.646.0700.15 | 1.666.0700.15 |
| PG 9 | 4 - 8 | ATEX | 6 | 21 | 17 | 1.616.0900.01 | 1.646.0900.01 | 1.666.0900.01 |
| PG 9 | 2 - 6 | ATEX | 6 | 21 | 17 | 1.616.0900.15 | 1.646.0900.15 | 1.666.0900.15 |
| PG 11 | 6 - 10 | ATEX | 6 | 22 | 20 | 1.616.1100.01 | 1.646.1100.01 | 1.666.1100.01 |
| PG 11 | 3 - 7 | ATEX | 6 | 22 | 20 | 1.616.1100.15 | 1.646.1100.15 | 1.666.1100.15 |
| PG 13,5 | 6 - 12 | ATEX | 6,5 | 24 | 22 | 1.616.1300.01 | 1.646.1300.01 | 1.666.1300.01 |
| PG 13,5 | 5 - 9 | ATEX | 6,5 | 24 | 22 | 1.616.1300.15 | 1.646.1300.15 | 1.666.1300.15 |
| PG 16 | 10 - 14 | ATEX | 6,5 | 23 | 24 | 1.616.1600.01 | 1.646.1600.01 | 1.666.1600.01 |
| PG 16 | 7 - 12 | ATEX | 6,5 | 23 | 24 | 1.616.1600.15 | 1.646.1600.15 | 1.666.1600.15 |
| PG 21 | 14 - 18 | ATEX | 7 | 24 | 30 | 1.616.2100.01 | 1.646.2100.01 | 1.666.2100.01 |
| PG 21 | 10 - 16 | ATEX | 7 | 24 | 30 | 1.616.2100.15 | 1.646.2100.15 | 1.666.2100.15 |
| PG 29 | 20 - 25 | ATEX | 8 | 29 | 40 | 1.616.2900.01 | 1.646.2900.01 | 1.666.2900.01 |
| PG 29 | 13 - 20 | ATEX | 8 | 29 | 40 | 1.616.2900.15 | 1.646.2900.15 | 1.666.2900.15 |
| PG 36 | 22 - 32 | ATEX | 8 | 35 | 50 | 1.616.3600.01 | 1.646.3600.01 | 1.666.3600.01 |
| PG 36 | 20 - 26 | ATEX | 8 | 35 | 50 | 1.616.3600.15 | 1.646.3600.15 | 1.666.3600.15 |
| PG 42 | 32 - 38 | ATEX | 9 | 37 | 57 | 1.616.4200.01 | 1.646.4200.01 | 1.666.4200.01 |
| PG 42 | 25 - 31 | ATEX | 9 | 37 | 57 | 1.616.4200.15 | 1.646.4200.15 | 1.666.4200.15 |
| PG 48 | 37 - 44 | ATEX | 10 | 38 | 64 | 1.616.4800.01 | 1.646.4800.01 | 1.666.4800.01 |
| PG 48 | 29 - 35 | ATEX | 10 | 38 | 64 | 1.616.4800.15 | 1.646.4800.15 | 1.666.4800.15 |

➔ Montagevejledning
side 168



HSK-M-EMV-D-Ex

Metr./Metr.-lang



ATEX





II 2G 1D
II 2G D

Materiale
Klemmeindsats
Pakning
O-ring
Tæthedegrad

Forniklet messing
PA
NBR
NBR
IP 68 – 10 bar / IP69K
i det angivne klemmeområde



For godkendelser se side 164


| AG |  mm | Ex- Generation | GL mm | H mm |  mm | Best.-Nr. -20°C – 95°C | Best.-Nr. -60°C – 105°C |
|---------------------|---|-------------------|----------|---------|---|---------------------------|----------------------------|
| M 16 x 1,5 | 5 - 10 | ATEX | 6 | 29 | 20 | 1.636.1600.50 | 1.637.1600.50 |
| M 20 x 1,5 | 10 - 14 | ATEX | 6 | 31 | 24 | 1.636.2000.50 | 1.637.2000.50 |
| M 25 x 1,5 | 13 - 18 | ATEX | 7 | 38 | 30 | 1.636.2500.50 | 1.637.2500.50 |
| M 32 x 1,5 | 18 - 25 | ATEX | 8 | 43 | 40 | 1.636.3200.50 | 1.637.3200.50 |
| M 40 x 1,5 | 24 - 32 | ATEX | 8 | 51 | 50 | 1.636.4000.50 | 1.637.4000.50 |
| Langt gevind | | | | | | | |
| M 16 x 1,5 | 5 - 10 | ATEX | 10 | 29 | 20 | 1.636.1600.30 | 1.637.1600.30 |
| M 20 x 1,5 | 10 - 14 | ATEX | 10 | 31 | 24 | 1.636.2000.30 | 1.637.2000.30 |
| M 25 x 1,5 | 13 - 18 | ATEX | 12 | 38 | 30 | 1.636.2500.30 | 1.637.2500.30 |
| M 32 x 1,5 | 18 - 25 | ATEX | 12 | 43 | 40 | 1.636.3200.30 | 1.637.3200.30 |
| M 40 x 1,5 | 24 - 32 | ATEX | 15 | 51 | 50 | 1.636.4000.30 | 1.637.4000.30 |

➔ Montagevejledning
side 168



HSK-M-EMV-D-Ex

PG



ATEX



II 2G 1D
II 2G D

Materiale
Klemmeindsats
Pakning
O-ring
Tæthedegrad

Forniklet messing
PA
NBR
NBR
IP 68 – 10 bar / IP69K
i det angivne klemmeområde

RoHS

For godkendelser se side 164
Kan også leveres med langt gevind



| AG | \varnothing mm | Ex- Generation | GL mm | H mm | \varnothing mm | Best.-Nr. -20 °C – 95 °C | Best.-Nr. -60 °C – 105 °C |
|---------|---------------------|-------------------|----------|---------|---------------------|-----------------------------|------------------------------|
| PG 11 | 5 - 10 | ATEX | 6 | 29 | 20 | 1.636.1100.01 | 1.637.1100.01 |
| PG 13,5 | 6 - 12 | ATEX | 6,5 | 31 | 22 | 1.636.1300.01 | 1.637.1300.01 |
| PG 16 | 10 - 14 | ATEX | 6,5 | 32 | 24 | 1.636.1600.01 | 1.637.1600.01 |
| PG 21 | 13 - 18 | ATEX | 7 | 38 | 30 | 1.636.2100.01 | 1.637.2100.01 |
| PG 29 | 18 - 25 | ATEX | 8 | 43 | 40 | 1.636.2900.01 | 1.637.2900.01 |
| PG 36 | 22 - 32 | ATEX | 8 | 48 | 50 | 1.636.3600.01 | 1.637.3600.01 |

➔ Montagevejledning
side 168



HSK-MZ-EMV/-PVDF-Ex

Metr./PG/NPT



Materiale
Klemmeindsats
Pakning
O-ring
Tæthedegrad

Forniklet messing
PA / PVDF
NBR / FPM
NBR / FPM
IP 68 – 10 bar / IP69K
i det angivne klemmeområde



For godkendelser se side 164
Kan også leveres med langt gevind

| AG | Ø mm | Ex- Generation | GL mm | H mm | L mm | Best.-Nr. | Best.-Nr. | Best.-Nr. |
|------------|---------|-------------------|----------|---------|---------|-------------------------------|--------------------------------|-------------------------------------|
| | | | | | | HSK-MZ-EMV-Ex -20°C – 95°C | HSK-MZ-EMV-Ex -60°C – 105°C | HSK-MZ-EMV-PVDF-Ex -20°C – 130°C |
| M 12 x 1,5 | 3 - 6,5 | ATEX | 6,5 | 26 | 14 | 1.617.1200.50 | 1.647.1200.50 | |
| M 16 x 1,5 | 6 - 10 | ATEX | 6 | 29 | 20 | 1.617.1600.50 | 1.647.1600.50 | |
| M 20 x 1,5 | 10 - 14 | ATEX | 6 | 32 | 24 | 1.617.2000.50 | 1.647.2000.50 | |
| M 25 x 1,5 | 14 - 18 | ATEX | 7 | 35 | 30 | 1.617.2500.50 | 1.647.2500.50 | |
| M 32 x 1,5 | 20 - 25 | ATEX | 8 | 41 | 40 | 1.617.3200.50 | 1.647.3200.50 | |
| M 40 x 1,5 | 24 - 32 | ATEX | 8 | 48 | 50 | 1.617.4000.50 | 1.647.4000.50 | |
| M 50 x 1,5 | 32 - 38 | ATEX | 9 | 51 | 57 | 1.617.5000.50 | 1.647.5000.50 | |
| M 50 x 1,5 | 28 - 31 | ATEX | 9 | 51 | 57 | 1.617.5000.51 | 1.647.5000.51 | |
| M 63 x 1,5 | 37 - 44 | ATEX | 10 | 52 | 68 | 1.617.6300.50 | 1.647.6300.50 | |
| M 63 x 1,5 | 32 - 35 | ATEX | 10 | 52 | 68 | 1.617.6300.51 | 1.647.6300.51 | |
| PG 7 | 3 - 6,5 | ATEX | 5 | 26 | 14 | 1.617.0700.01 | 1.647.0700.01 | 1.667.0700.01 |
| PG 9 | 4 - 8 | ATEX | 6 | 28 | 17 | 1.617.0900.01 | 1.647.0900.01 | 1.667.0900.01 |
| PG 11 | 6 - 10 | ATEX | 6 | 29 | 20 | 1.617.1100.01 | 1.647.1100.01 | 1.667.1100.01 |
| PG 13,5 | 7 - 12 | ATEX | 6,5 | 33 | 22 | 1.617.1300.01 | 1.647.1300.01 | 1.667.1300.01 |
| PG 16 | 10 - 14 | ATEX | 6,5 | 32 | 24 | 1.617.1600.01 | 1.647.1600.01 | 1.667.1600.01 |
| PG 21 | 13 - 18 | ATEX | 7 | 35 | 30 | 1.617.2100.01 | 1.647.2100.01 | 1.667.2100.01 |
| PG 29 | 20 - 25 | ATEX | 8 | 41 | 40 | 1.617.2900.01 | 1.647.2900.01 | 1.667.2900.01 |
| PG 36 | 24 - 32 | ATEX | 8 | 48 | 50 | 1.617.3600.01 | 1.647.3600.01 | 1.667.3600.01 |
| PG 42 | 32 - 38 | ATEX | 9 | 51 | 57 | 1.617.4200.01 | 1.647.4200.01 | 1.667.4200.01 |
| PG 42 | 28 - 31 | ATEX | 9 | 51 | 57 | 1.617.4200.15 | 1.647.4200.15 | 1.667.4200.15 |
| PG 48 | 37 - 44 | ATEX | 10 | 51 | 64 | 1.617.4800.01 | 1.647.4800.01 | 1.667.4800.01 |
| PG 48 | 32 - 35 | ATEX | 10 | 51 | 64 | 1.617.4800.15 | 1.647.4800.15 | 1.667.4800.15 |
| 3/8" NPT | 4 - 8 | ATEX | 15 | 27 | 17 / 19 | 1.617.3800.70 | 1.647.3800.70 | 1.667.3800.70 |
| 1/2" NPT | 7 - 12 | ATEX | 13 | 31 | 22 / 24 | 1.617.1200.70 | 1.647.1200.70 | 1.667.1200.70 |
| 3/4" NPT | 13 - 18 | ATEX | 13 | 36 | 30 | 1.617.3400.70 | 1.647.3400.70 | 1.667.3400.70 |

➔ Montagevejledning
side 168

