




Den sikre forbindelse



KOBBER

RØRKABELSKO

For ledertype: Flerkorede
Overflade: Galvanisk forfinnet
Med inspektionshul



Lednings- tværsnit i mm ²	Bolt Ø mm	Best. nr.	EAN-nr.	Mål i mm									Antal pr. pagn.
				d ₁	a	b	d ₂	d ₄	c ₁	c ₂	l		
0,75	M 3	91R/3	40 12078 001465	1,3	6	6	3,2	2,8	3,25	4	12	100	
	M 4	91R/4	40 12078 001489	1,3	6	6,5	4,3	2,8	4	5	13	100	
	M 5	91R/5	40 12078 001502	1,3	6	7,5	5,3	2,8	4,75	5,5	14	100	
1,5	M 3	92R/3	40 12078 001526	1,8	6	6,5	3,2	3,3	3,25	4	12	100	
	M 4	92R/4	40 12078 001540	1,8	6	6,5	4,3	3,3	4	5	13	100	
	M 5	92R/5	40 12078 001564	1,8	6	7,5	5,3	3,3	4,75	5,5	14	100	
	M 6	92R/6	40 12078 001588	1,8	6	9	6,5	3,3	6,5	6,5	16	100	
2,5	M 3	93R/3	40 12078 001601	2,3	6	7,5	3,2	4,2	3,25	4	12	100	
	M 4	93R/4	40 12078 001625	2,3	6	7,5	4,3	4,2	4	5	13	100	
	M 5	93R/5	40 12078 001649	2,3	6	8,5	5,3	4,2	4,75	5,5	14	100	
	M 6	93R/6	40 12078 001663	2,3	6	9,5	6,5	4,2	6,5	6,5	16	100	
	M 8	93R/8	40 12078 001687	2,3	6	13	8,5	4,2	7,75	9,5	20	100	
4	M 4	94R/4	40 12078 001694	3	8	8,5	4,3	5	4,75	5,5	17	100	
	M 5	94R/5	40 12078 001717	3	8	9	5,3	5	4,75	6	17	100	
	M 6	94R/6	40 12078 001731	3	8	10	6,5	5	6,5	6,5	19	100	
	M 8	94R/8	40 12078 001755	3	8	13	8,5	5	8,5	9,5	22	100	
6	M 5	1R/ 5	40 12078 002677	3,5	9	10	5,5	6,5	6,5	7,5	21	100	
	M 6	1R/ 6	40 12078 002684	3,5	9	12	6,5	6,5	6,5	7,5	21	100	
	M 8	1R/ 8	40 12078 002691	3,5	9	15	8,5	6,5	10	10	23	100	
	M10	1R/10	40 12078 002707	3,5	9	17	10,5	6,5	12	12	25	100	
	M12	1R/12	40 12078 002714	3,5	9	19	13	6,5	13	13	28	100	
10	M 5	2R/ 5	40 12078 002721	4,5	10	12	5,5	7	6,5	7,5	22	100	
	M 6	2R/ 6	40 12078 002738	4,5	10	12	6,5	7	6,5	7,5	22	100	
	M 8	2R/ 8	40 12078 002745	4,5	10	15	8,5	7	10	10	25	100	
	M10	2R/10	40 12078 002752	4,5	10	17	10,5	7	12	12	27	100	
	M12	2R/12	40 12078 002769	4,5	10	19	13	7	13	13	29	100	
16	M 5	3R/ 5	40 12078 002776	5,5	13	12	5,5	8,5	5,5	6,5	26	100	
	M 6	3R/ 6	40 12078 002783	5,5	13	12	6,5	8,5	6,25	7,5	27	100	
	M 8	3R/ 8	40 12078 002790	5,5	13	15	8,5	8,5	8,5	9,5	29	100	
	M10	3R/10	40 12078 002806	5,5	13	17	10,5	8,5	10,5	11,5	31	100	
	M12	3R/12	40 12078 002813	5,5	13	19	13	8,5	12	13	33	100	




PRESSEVÆRKTØJ
- se afsnit

KOBBER

RØRKABELSKO

For ledertype: Flerkorede
Overflade: Galvanisk fortinnet
Med inspektionshul




Lednings- tværsnit i mm ²	Bolt Ø mm	Best. nr.	EAN-nr.	Mål i mm								Antal pr. pakk.
				d ₁	a	b	d ₂	d ₄	c ₁	c ₂	l	
25	M 5	4R/ 5	40 12078 002820	7	15	14	5,5	10	7,5	7,5	30	100
	M 6	4R/ 6	40 12078 002837	7	15	14	6,5	10	7,5	7,5	30	100
	M 8	4R/ 8	40 12078 002844	7	15	16	8,5	10	10	10	32	100
	M10	4R/10	40 12078 002851	7	15	18	10,5	10	12	12	34	100
	M12	4R/12	40 12078 002868	7	15	19	13	10	13	13	35	100
	M14	4R/14	40 12078 002875	7	15	21	15	10	14,5	14,5	38	100
35	M 6	5R/ 6	40 12078 002882	8,5	17	17	6,5	12	7,5	7,5	32	100
	M 8	5R/ 8	40 12078 002899	8,5	17	17	8,5	12	10	10	34	100
	M10	5R/10	40 12078 002905	8,5	17	19	10,5	12	12	12	37	100
	M12	5R/12	40 12078 002912	8,5	17	21	13	12	13	13	38	100
	M14	5R/14	40 12078 002929	8,5	17	21	15	12	14,5	14,5	40	100
	M16	5R/16	40 12078 002936	8,5	17	26	17	12	16	16	42	100
50	M 6	6R/ 6	40 12078 002943	10	19	20	6,5	14	10	10	37	100
	M 8	6R/ 8	40 12078 002950	10	19	20	8,5	14	10	10	37	100
	M10	6R/10	40 12078 002967	10	19	20	10,5	14	12	13	39	100
	M12	6R/12	40 12078 002974	10	19	23	13	14	13	13	43	100
	M14	6R/14	40 12078 002981	10	19	23	15	14	14,5	14,5	45	100
	M16	6R/16	40 12078 002998	10	19	28	17	14	16	16	46	100
	M20	6R/20	40 12078 003001	10	19	30	21	14	19	19	48	100
70	M 6	7R/ 6	40 12078 003018	12	21	23	6,5	16,5	10	10	43	100
	M 8	7R/ 8	40 12078 003025	12	21	23	8,5	16,5	10	10	43	100
	M10	7R/10	40 12078 003032	12	21	23	10,5	16,5	12	12	44	100
	M12	7R/12	40 12078 003049	12	21	23	13	16,5	13	13	46	100
	M14	7R/14	40 12078 003056	12	21	23	15	16,5	14,5	14,5	48	100
	M16	7R/16	40 12078 003063	12	21	28	17	16,5	16	16	50	100
	M20	7R/20	40 12078 003070	12	21	30	21	16,5	19	19	53	100
95	M 8	8R/ 8	40 12078 003087	13,5	25	26	8,5	18	12	12	48	50
	M10	8R/10	40 12078 003094	13,5	25	26	10,5	18	12	12	48	50
	M12	8R/12	40 12078 003100	13,5	25	26	13	18	13	13	49	50
	M14	8R/14	40 12078 003117	13,5	25	26	15	18	14,5	14,5	51	50
	M16	8R/16	40 12078 003124	13,5	25	28	17	18	16	16	54	50
	M20	8R/20	40 12078 003131	13,5	25	36	21	18	22	22	60	50
120	M 8	9R/ 8	40 12078 003148	15	26	28	8,5	19,5	14	14	51	50
	M10	9R/10	40 12078 003155	15	26	28	10,5	19,5	14	14	51	50
	M12	9R/12	40 12078 003162	15	26	28	13	19,5	14	14	51	50
	M14	9R/14	40 12078 003179	15	26	28	15	19,5	15	15	52	50
	M16	9R/16	40 12078 003186	15	26	30	17	19,5	16	16	54	50
	M20	9R/20	40 12078 003193	15	26	36	21	19,5	22	22	63	50

PRESSEVÆRKTØJ
- se afsnit

KOBBER

RØRKABELSKO

For ledertype: Flerkorede
Overflade: Galvanisk forfinnet
Med inspektionshul



Lednings- tværsnit i mm ²	Bolt Ø mm	Best. nr.	EAN-nr.	Mål i mm								Antal pr. pakn.
				d ₁	a	b	d ₂	d ₄	c ₁	c ₂	l	
150	M 8	10R/ 8	40 12078 002431	16,5	30	31	8,5	21	14	14	56	50
	M10	10R/10	40 12078 002448	16,5	30	31	10,5	21	14	14	56	50
	M12	10R/12	40 12078 003223	16,5	30	31	13	21	15	15	57	50
	M14	10R/14	40 12078 003230	16,5	30	31	15	21	15	15	57	50
	M16	10R/16	40 12078 003247	16,5	30	31	17	21	16	16	58	50
	M20	10R/20	40 12078 003254	16,5	30	36	21	21	22	22	66	50
185	M10	11R/10	40 12078 002493	19	30	35	10,5	24	18	18	65	50
	M12	11R/12	40 12078 003278	19	30	35	13	24	18	18	65	50
	M14	11R/14	40 12078 003285	19	30	35	15	24	18	18	65	50
	M16	11R/16	40 12078 003292	19	30	35	17	24	18	18	65	50
	M20	11R/20	40 12078 003308	19	30	39	21	24	22	22	69	50
	240	M10	12R/10	40 12078 003315	21	35	39	10,5	26	21,5	19	72
M12		12R/12	40 12078 003322	21	35	39	13	26	21,5	19	72	50
M14		12R/14	40 12078 003339	21	35	39	15	26	21,5	19	72	50
M16		12R/16	40 12078 003346	21	35	39	17	26	21,5	19	72	50
M20		12R/20	40 12078 003353	21	35	39	21	26	21,5	19	72	50
300		M12	13R/12	40 12078 002592	23,5	44	43	13	29,5	24	24	87
	M14	13R/14	40 12078 003377	23,5	44	43	15	29,5	24	24	87	25
	M16	13R/16	40 12078 003384	23,5	44	43	17	29,5	24	24	87	25
	M20	13R/20	40 12078 003391	23,5	44	43	21	29,5	24	24	87	25
	400	M12	14R/12	40 12078 003407	27	44	49	13	34	24	24	90
M14		14R/14	40 12078 003414	27	44	49	15	34	24	24	90	20
M16		14R/16	40 12078 002653	27	44	49	17	34	24	24	90	20
M20		14R/20	40 12078 003438	27	44	49	21	34	24	24	90	20
500		M16	115R/16	40 12078 011433	31	65	60	17	42			126
	M20	115R/20	40 12078 011440	31	65	60	21	42			126	10
625	M16	116R/16	40 12078 011457	35	78	64	17	44			135	5
	M20	116R/20	40 12078 011464	35	78	64	21	44			135	5
800	M16	117R/16	40 12078 011471									




PRESSEVÆRKTØJ
- se afsnit

KOBBER

VINKEL RØRKABELSKO

90° vinkel
 For ledertype: Flerkorede
 Overflade: Galvanisk fortinnet



Lednings- tværsnit i mm ²	Bolt Ø mm	Best. nr.	EAN-nr.	Mål i mm								Antal pr. pagn.
				d ₁	a	b	d ₂	d ₄	c ₁	l ₃		
6	M 6	41R/ 6	40 12078 003469	3,5	9	12	6,5	6,5	7,5	10	100	
10	M 6	42R/ 6	40 12078 003568	4,5	10	12	6,5	7	6,5	10	100	
16	M 8	43R/ 8	40 12078 003681	5,5	13	15	8,5	8,5	10	13	100	
25	M 8	44R/ 8	40 12078 003780	7	15	16	8,5	10	10	13	100	
35	M 8	45R/ 8	40 12078 003889	8,5	17	17	8,5	12	10	13	100	
50	M10	46R/10	40 12078 004022	10	19	20	10,5	14	12	16	100	
70	M10	47R/10	40 12078 004169	12	21	23	10,5	16,5	12	16	100	
95	M12	48R/12	40 12078 004305	13,5	25	26	13	18	13	18	50	
120	M12	49R/12	40 12078 004428	15	26	28	13	19,5	14	18	50	
150	M12	50R/12	40 12078 004541	16,5	30	31	13	21	15	18	50	
185	M16	51R/16	40 12078 004688	19	30	35	17	24	18	22	25	
240	M16	52R/16	40 12078 004787	21	35	39	17	26	21,5	22	25	
300	M20	53R/20	40 12078 004886	23,5	44	43	21	29,5	24	24	20	
400	M20	54R/20	40 12078 004961	27	44	49	21	34	24	24	10	

PRESSEVÆRKTØJ
 - se afsnit

KOBBER

VINKEL RØRKABELSKO

45° vinkel
 For ledertype: Flerkorede
 Overflade: Galvanisk fortinnet



Lednings- tværsnit i mm ²	Bolt Ø mm	Best. nr.	EAN-nr.	Mål i mm							Antal pr. pakn.
				d ₁	a	b	d ₂	d ₄	c ₁	l ₃	
6	M 6	41R/ 6-45	40 12078 003476	3,5	9	12	6,5	6,5	7,5	10	100
10	M 6	42R/ 6-45	40 12078 003575	4,5	10	12	6,5	7	6,5	10	100
16	M 8	43R/ 8-45	40 12078 003698	5,5	13	15	8,5	8,5	10	13	100
25	M 8	44R/ 8-45	40 12078 003797	7	15	16	8,5	10	10	13	100
35	M 8	45R/ 8-45	40 12078 003896	8,5	17	17	8,5	12	10	13	100
50	M10	46R/10-45	40 12078 004039	10	19	20	10,5	14	12	16	100
70	M10	47R/10-45	40 12078 004176	12	21	23	10,5	16,5	12	16	100
95	M12	48R/12-45	40 12078 004312	13,5	25	26	13	18	13	18	50
120	M12	49R/12-45	40 12078 004435	15	26	28	13	19,5	14	18	50
150	M12	50R/12-45	40 12078 004558	16,5	30	31	13	21	15	18	50
185	M16	51R/16-45	40 12078 004695	19	30	35	17	24	18	22	25
240	M16	52R/16-45	40 12078 004794	21	35	39	17	26	21,5	22	25
300	M20	53R/20-45	40 12078 004893	23,5	44	43	21	29,5	24	24	20
400	M20	54R/20-45	40 12078 004978	27	44	49	21	34	24	24	10




PRESSEVÆRKTØJ
 - se afsnit

KOBBER

RØRKABELSKO

For ledertype: Mangetrådede
Overflade: Galvanisk fortinnet

Med inspektionshul og
tragtformet åbning for lettere kabelindføring



Lednings- tværsnit i mm ²	Bolt Ø mm	Best. nr.	EAN-nr.	Mål i mm								Antal pr. pagn.
				d ₁	a	b	d ₂	d ₄	c ₁	c ₂	l	
10	M 5	702F/ 5	40 12078 043571	5,5	14	12	5,3	8	6,25	7,5	27	100
	M 6	702F/ 6	40 12078 043595	5,5	14	12	6,5	8	6,25	7,5	27	100
	M 8	702F/ 8	40 12078 043618	5,5	14	16	8,5	8	8,5	9,5	29	100
	M10	702F/10	40 12078 043632	5,5	14	16	10,5	8	10,5	11,5	31	100
	M12	702F/12	40 12078 043656	5,5	14	19	13	8	12	13	32	100
16	M 5	703F/ 5	40 12078 043670	6,6	15	13	5,3	9,5	6,25	7,5	30	100
	M 6	703F/ 6	40 12078 043694	6,6	15	13	6,5	9,5	6,25	7,5	30	100
	M 8	703F/ 8	40 12078 043717	6,6	15	16	8,5	9,5	10	10	32	100
	M10	703F/10	40 12078 043731	6,6	15	17	10,5	9,5	12	12	34	100
	M12	703F/12	40 12078 043755	6,6	15	19	13	9,5	13	13	35	100
25	M 5	704F/ 5	40 12078 043779	7,9	17	15	5,3	11	7,5	7,5	32	100
	M 6	704F/ 6	40 12078 043793	7,9	17	15	6,5	11	7,5	7,5	32	100
	M 8	704F/ 8	40 12078 043816	7,9	17	17	8,5	11	10	10	34	100
	M10	704F/10	40 12078 043830	7,9	17	17	10,5	11	12	12	37	100
	M12	704F/12	40 12078 043854	7,9	17	19	13	11	13	13	38	100
35	M 6	705F/ 6	40 12078 043878	9,2	19	17	6,5	12,5	7,5	7,5	35	100
	M 8	705F/ 8	40 12078 043892	9,2	19	18	8,5	12,5	10	10	37	100
	M10	705F/10	40 12078 043915	9,2	19	18	10,5	12,5	12	12	40	100
	M12	705F/12	40 12078 043939	9,2	19	19	13	12,5	13	13	41	100
	M14	705F/14	40 12078 043953	9,2	19	21	15	12,5	14,5	14,5	43	100
50	M 6	706F/ 6	40 12078 043977	11	21	21	6,5	15	10	10	41	100
	M 8	706F/ 8	40 12078 043991	11	21	21	8,5	15	10	10	41	100
	M10	706F/10	40 12078 044011	11	21	21	10,5	15	12	12	43	100
	M12	706F/12	40 12078 044035	11	21	21	13	15	13	13	46	100
	M14	706F/14	40 12078 044059	11	21	23	15	15	14,5	14,5	48	100
	M16	706F/16	40 12078 044073	11	21	28	17	15	16	16	50	100
70	M 8	707F/ 8	40 12078 044097	13	25	25	8,5	17	10	10	46	50
	M10	707F/10	40 12078 044110	13	25	25	10,5	17	12	12	48	50
	M12	707F/12	40 12078 044134	13	25	25	13	17	13	13	50	50
	M14	707F/14	40 12078 044158	13	25	25	15	17	14,5	14,5	52	50
	M16	707F/16	40 12078 044172	13	25	25	17	17	16	16	54	50


PRESSEVÆRKTØJ
- se afsnit

KOBBER

RØRKABELSKO

For ledertype: Mangetrådede
Overflade: Galvanisk fortinnet

Med inspektionshul og
tragtformet åbning for lettere kabelindføring




Lednings- tværsnit i mm ²	Bolt Ø mm	Best. nr.	EAN-nr.	Mål i mm								Antal pr. pakn.
				d ₁	a	b	d ₂	d ₄	c ₁	c ₂	l	
95	M 8	708F/ 8	40 12078 044196	14,5	26	28	8,5	19	12	12	52	50
	M10	708F/10	40 12078 044219	14,5	26	28	10,5	19	12	12	52	50
	M12	708F/12	40 12078 044233	14,5	26	28	13	19	13	13	53	50
	M14	708F/14	40 12078 044257	14,5	26	28	15	19	14,5	14,5	55	50
	M16	708F/16	40 12078 044271	14,5	26	28	17	19	16	16	56	50
120	M10	709F/10	40 12078 044295	16,2	30	30	10,5	21	14	14	57	50
	M12	709F/12	40 12078 044318	16,2	30	30	13	21	15	15	58	50
	M14	709F/14	40 12078 044332	16,2	30	30	15	21	15	15	58	50
	M16	709F/16	40 12078 044356	16,2	30	30	17	21	16	16	59	50
	M20	709F/20	40 12078 044370	16,2	30	36	21	21	22	22	66	50
150	M10	710F/10	40 12078 044394	18	32	34	10,5	23	15	16	64	50
	M12	710F/12	40 12078 044417	18	32	34	13	23	16	17	65	50
	M14	710F/14	40 12078 044431	18	32	34	15	23	18	19	67	50
	M16	710F/16	40 12078 044455	18	32	34	17	23	19	20	68	50
	M20	710F/20	40 12078 044479	18	32	40	21	23	21	22	70	50
185	M12	711F/12	40 12078 044493	20,6	35	39	13	26	21,5	19	72	50
	M14	711F/14	40 12078 044516	20,6	35	39	15	26	21,5	19	72	50
	M16	711F/16	40 12078 044530	20,5	35	39	17	26	21,5	19	72	50
	M20	711F/20	40 12078 044554	20,6	35	39	21	26	21,5	19	72	50
240	M12	712F/12	40 12078 044578	23,1	44	41	13	28	16	17	80	25
	M14	712F/14	40 12078 044592	23,1	44	41	15	28	19	20	83	25
	M16	712F/16	40 12078 044615	23,1	44	41	17	28	19	20	83	25
	M20	712F/20	40 12078 044639	23,1	44	41	21	28	21	22	85	25
300	M12	713F/12	40 12078 044653	26,1	44	47	13	32	19	22	96	20
	M14	713F/14	40 12078 044677	26,1	44	47	15	32	19	22	96	20
	M16	713F/16	40 12078 044691	26,1	44	47	17	32	19	22	96	20
	M20	713F/20	40 12078 044714	26,1	44	47	21	32	22	22	96	20








PRESSEVÆRKTØJ
- se afsnit

ISOLEREDE RØRKABELSKO

Materiale: Kobber med PA-isolering
For ledertype: Mangetrådede
Overflade: Galvanisk fortinnet
Med inspektionshul




Lednings- tværsnit i mm ²	Bolt Ø mm	Best. nr.	EAN-nr.	Mål i mm					Farve	Antal pr. pakn.
				d ₂	d ₁₂	d ₁₃	Gl ₁	l ₁₀		
 10	M 5	602R/ 5	40 12078 009294	5,5	7	9	35,5	17	rød	100
	M 6	602R/ 6	40 12078 009300	6,5	7	9	35,5	17	rød	100
	M 8	602R/ 8	40 12078 009317	8,5	7	9	42	17	rød	100
	M10	602R/10	40 12078 009324	10,5	7	9	46	17	rød	100
	M12	602R/12	40 12078 009331	13	7	9	49	17	rød	100
 16	M 5	603R/ 5	40 12078 009348	5,5	8,5	10,5	39,5	21	blå	100
	M 6	603R/ 6	40 12078 009355	6,5	8,5	10,5	41,3	21	blå	100
	M 8	603R/ 8	40 12078 008822	8,5	8,5	10,5	45,5	21	blå	100
	M10	603R/10	40 12078 009379	10,5	8,5	10,5	49,5	21	blå	100
	M12	603R/12	40 12078 009386	13	8,5	10,5	54	21	blå	100
 25	M 5	604R/ 5	40 12078 009393	5,5	10	12	45	24	gul	100
	M 6	604R/ 6	40 12078 009409	6,5	10	12	46,5	24	gul	100
	M 8	604R/ 8	40 12078 009416	8,5	10	12	51	24	gul	100
	M10	604R/10	40 12078 009423	10,5	10	12	55	24	gul	100
	M12	604R/12	40 12078 009430	13	10	12	57	24	gul	100
	M14	604R/14	40 12078 009447	15	10	12	61,5	24	gul	100
 35	M 6	605R/ 6	40 12078 009454	6,5	12	14,5	49,5	27	rød	100
	M 8	605R/ 8	40 12078 009461	8,5	12	14,5	54	27	rød	100
	M10	605R/10	40 12078 009478	10,5	12	14,5	59	27	rød	100
	M12	605R/12	40 12078 009485	13	12	14,5	61	27	rød	100
	M14	605R/14	40 12078 009492	15	12	14,5	64,5	27	rød	100
	M16	605R/16	40 12078 009560	17	12	14,5	68	27	rød	100
 50	M 6	606R/ 6	40 12078 009515	6,5	14	16,5	59	32	blå	100
	M 8	606R/ 8	40 12078 009522	8,5	14	16,5	59	32	blå	100
	M10	606R/10	40 12078 009539	10,5	14	16,5	63	32	blå	100
	M12	606R/12	40 12078 009546	13	14	16,5	68	32	blå	100
	M14	606R/14	40 12078 009553	15	14	16,5	71,5	32	blå	100
	M16	606R/16	40 12078 009560	17	14	16,5	77	32	blå	100
	M20	606R/20	40 12078 009577	21	14	16,5	83,5	32	blå	100

PRESSEVÆRKTØJ
- se afsnit

ISOLEREDE RØRKABELSKO

Materiale: Kobber med PA-isolering
For ledertype: Mangetrådede
Overflade: Galvanisk forfinnet
Med inspektionshul



Lednings- tværsnit i mm ²	Bolt Ø mm	Best. nr.	EAN-nr.	Mål i mm					Farve	Antal pr. pakn.
				d ₂	d ₁₂	d ₁₃	Gl ₁	l ₁₀		
70	M 6	607R/ 6	40 12078 009584	6,5	16,4	18,9	65,5	33,5	gul	50
	M 8	607R/ 8	40 12078 009591	8,5	16,4	18,9	65,5	33,5	gul	50
	M10	607R/10	40 12078 009607	10,5	16,4	18,9	66,5	33,5	gul	50
	M12	607R/12	40 12078 009614	13	16,4	18,9	70,5	33,5	gul	50
	M14	607R/14	40 12078 009621	15	16,4	18,9	73,5	33,5	gul	50
	M16	607R/16	40 12078 009638	17	16,4	18,9	78,5	33,5	gul	50
	M20	607R/20	40 12078 009645	21	16,4	18,9	84,5	33,5	gul	50
95	M 8	608R/ 8	40 12078 009652	8,5	17,8	20,8	74	40	rød	50
	M10	608R/10	40 12078 009669	10,5	17,8	20,8	74	40	rød	50
	M12	608R/12	40 12078 009676	13	17,8	20,8	76	40	rød	50
	M14	608R/14	40 12078 009683	15	17,8	20,8	79,5	40	rød	50
	M16	608R/16	40 12078 009690	17	17,8	20,8	84	40	rød	50
	M20	608R/20	40 12078 009706	21	17,8	20,8	96	40	rød	50
120	M 8	609R/ 8	40 12078 009713	8,5	19,3	22,3	80,5	41,5	blå	50
	M10	609R/10	40 12078 009720	10,5	19,3	22,3	80,5	41,5	blå	50
	M12	609R/12	40 12078 009737	13	19,3	22,3	80,5	41,5	blå	50
	M14	609R/14	40 12078 009744	15	19,3	22,3	82,5	41,5	blå	50
	M16	609R/16	40 12078 009751	17	19,3	22,3	85,5	41,5	blå	50
	M20	609R/20	40 12078 009768	21	19,3	22,3	100,5	41,5	blå	50
	150	M 8	610R/ 8	40 12078 009775	8,5	20,8	23,8	88	48	gul
M10		610R/10	40 12078 009782	10,5	20,8	23,8	88	48	gul	25
M12		610R/12	40 12078 009799	13	20,8	23,8	89	48	gul	25
M14		610R/14	40 12078 009805	15	20,8	23,8	90	48	gul	25
M16		610R/16	40 12078 009812	17	20,8	23,8	92	48	gul	25
M20		610R/20	40 12078 009829	21	20,8	23,8	106	48	gul	25




PRESSEVÆRKTØJ
- se afsnit

KOBBER

RØRSAMLEMUFFER

For ledertype: Flerkorede
Overflade: Galvanisk fortinnet




Lednings- tværsnit i mm ²	Best. nr.	EAN-nr.	Mål i mm			Antal pr. pagn.
			d ₁	d ₄	l	
0,75	17R	40 12078 004985	1,3	2,8	20	100
1,5	18R	40 12078 004992	1,8	3,3	25	100
2,5	19R	40 12078 001601	2,3	4,2	25	100
4	20R	40 12078 005012	3	5	25	100
6	21R	40 12078 005029	3,5	6,5	25	100
10	22R	40 12078 005036	4,5	7	30	100
16	23R	40 12078 005043	5,5	8,5	35	100
25	24R	40 12078 005050	7	10	40	100
35	25R	40 12078 005067	8,5	12	45	100
50	26R	40 12078 005074	10	14	50	100
70	27R	40 12078 005081	12	16,5	55	100
95	28R	40 12078 005098	13,5	18	60	50
120	29R	40 12078 005104	15	19,5	65	50
150	30R	40 12078 005111	16,5	21	70	50
185	31R	40 12078 005128	19	24	75	25
240	32R	40 12078 005135	21	26	85	25
300	33R	40 12078 005142	23,5	29,5	100	25
400	34R	40 12078 005159	27	34	100	10

PRESSEVÆRKTØJ
- se afsnit

ISOLEREDE RØRSAMLEMUFFER

Materiale: Kobber med PA-isolering
Overflade: Galvanisk fortinnet




Lednings- tværsnit i mm ²	Best. nr.	EAN-nr.	Mål i mm			Farve	Antal pr. pakn.	
			d ₁₃	d ₁₂	l ₁₀			
10	622R	40 12078 010757	9	7	42	rød	100	
16	623R	40 12078 010764	10,5	8,5	50	blå	100	
25	624R	40 12078 010771	12	10	57	gul	100	
35	625R	40 12078 010788	14,4	12	65	rød	100	
50	626R	40 12078 010795	16,4	14	72	blå	100	
70	627R	40 12078 010801	19	16,4	80	gul	50	
95	628R	40 12078 010818	20,8	17,8	87	rød	50	
120	629R	40 12078 010825	22,3	19,3	94	blå	25	
150	630R	40 12078 010832	23,8	20,8	103	gul	25	

PRESSEVÆRKTØJ
- se afsnit

KOBBER

UDLIGNINGSTYLLER

For ledertype: Flerkorede
Overflade: Galvanisk forfinnet





Lednings- tværsnit i mm ²	Best. nr.	EAN-nr.	Mål i mm		
			d ₁	d ₄	l
16	VHR 16	40 12078 008310	5	5,3	11
25	VHR 25	40 12078 008327	6,4	6,7	14
35	VHR 35	40 12078 008334	7,7	8,2	15
50	VHR 50	40 12078 008341	9	9,5	18
70	VHR 70	40 12078 008358	10,6	11,2	19
95	VHR 95	40 12078 008365	12,4	13	21
120	VHR 120	40 12078 008372	13,9	14,5	22
150	VHR 150	40 12078 008389	15,4	16	26
185	VHR 185	40 12078 008396	17,6	18,2	26
240	VHR 240	40 12078 008402	19,9	20,5	30
300	VHR 300	40 12078 008419	22,4	23	38
400	VHR 400	40 12078 008426	25,4	26,2	38

PRESSEVÆRKTØJ
- se afsnit

C-KLEMMER

Materiale : Kobber
 For ledertype: Runde, flerkorede og massive
 Overflade: Galvanisk fortinnet



Lednings- tværsnit i mm ² Gennemgang rund flerkoret/ rund massiv	Afgrening rund flerkoret/ rund massiv	Best. nr.	EAN-nr.	Mål i mm		
				b	l	
16/25	16/25	CK 16	40 12078 008259	16	15	
25/35	25/35	CK 25	40 12078 008273	20	16	
35/50	35/50	CK 35	40 12078 008280	26	22	
50/-	50/-	CK 50	40 12078 008297	28	23	
70/-	70/-	CK 70	40 12078 008303	34	28	KONTAKTFEDT FOR C-KLEMMER Best.nr. KF 125 EAN-nummer 40 12078 019538 Dåse med 0,125 kg <i>PRESSEVÆRKTØJ - se afsnit</i>