



ZMVV.E250316 Wire Connectors and Soldering Lugs

[Page Bottom](#)

Wire Connectors and Soldering Lugs

[See General Information for Wire Connectors and Soldering Lugs](#)

GUSTAV KLAUKE GMBH
AUF DEM KNAPP 46
42855 REMSCHEID, GERMANY

E250316

Pressure cable connectors, butt-type, "L Series", Model(s) LV0.75, LV1.5, LV2.5, LV4, LV6, LV10, LV16, LV25, LV35, LV50, LV70, LV95, LV120, LV150, LV185, LV240, LV300, LV400, LV500, or LV630, may be followed by Suffix bk.

Pressure cable connectors, butt-type, "NDC Series", Model(s) NDC0.75L, NDC1.5L, NDC2.5L, NDC4L, NDC6L, NDC10L, NDC16L, NDC25L, NDC35L, NDC50L, NDC70L, NDC95L, NDC120L, NDC150L, NDC185L, NDC240L, NDC300L, NDC400L, NDC500L, NDC630L.

Pressure cable connectors, butt-type, "R Series", Model(s) 17R, 18R, 19R, 20R, 21R, 22R, 23R, 24R, 25R, 26R, 27R, 28R, 29R, 30R, 31R, 32R, 33R, 34R, or 35R, may be followed by Suffix bk, or Pb.

Pressure cable connectors, cross connectors, "L Series", Model(s) KVL1.5, KVL2.5, KVL4, KVL6, KVL10, KVL16, KVL25, KVL35, KVL50, KVL70, KVL95, KVL120, KVL150, KVL185, or KVL240, may be followed by Suffix bk.

Pressure cable connectors, cross-connectors, "R Series", Model(s) KV1.5, KV2.5, KV4, KV6, KV10, KV16, KV25, KV35, KV50, KV70, KV95, KV120, KV150, KV185, or KV240, may be followed by Suffix bk, or Pb.

Pressure cable connectors, T-connectors, "L Series", Model(s) TVL1.5, TVL2.5, TVL4, TVL6, TVL10, TVL16, TVL25, TVL35, TVL50, TVL70, TVL95, TVL120, TVL150, TVL185, or TVL240, may be followed by Suffix bk.

Pressure cable connectors, T-connectors, "R Series", Model(s) TV1.5, TV2.5, TV4, TV6, TV10, TV16, TV25, TV35, TV50, TV70, TV95, TV120, TV150, TV185, or TV240, may be followed by Suffix bk, or Pb.

Pressure terminal connectors, narrow palm type, "R Series", Model(s) 5SG, 6SG, 7SG, 8SG, 9SG, 10SG, 11SG, 12SG, or 13SG, followed by /1 or 2-digit number, may be followed by Suffix bk.

Pressure terminal connectors, angled-45 degree, "R Series", Model(s) 41R, 42R, 43R, 44R, 45R, 46R, 47R, 48R, 49R, 50R, 51R, 52R, 53R, or 54R, followed by a /1 or /2-digit number, and by Suffix -45, may be followed by Suffix bk, or Pb.

Pressure terminal connectors, angled-45 degrees, "L Series", Model(s) L6, L10, L16, L25, L35, L50, L70, L95, L120, L150, L185, L240, L300, L400, followed by a /1 or /2-digit number, and by suffix -45, may be followed by Suffix bk.

Pressure terminal connectors, angled-90 degree, "R Series", Model(s) 41R, 42R, 43R, 44R, 45R, 46R, 47R, 48R, 49R, 50R, 51R, 52R, 53R or 54R, followed by a /1 or /2-digit number, may be followed by Suffix bk, or Pb.

Pressure terminal connectors, angled-90 degrees, "F Series", Model(s) Cat. Nos. 742F5, 742F6, 742F8, 742F10, 742F12, 743F5, 743F6, 743F8, 743F10, 743F12, 744F5, 744F6, 744F8, 744F10, 744F12, 745F6, 745F8, 745F10, 745F12, 745F14, 746F6, 746F8, 746F10, 746F12, 746F14, 746F16, 747F8, 747F10, 747F12, 747F14, 747F16, 748F8, 748F10, 748F12, 748F14, 748F16, 749F10, 749F12, 749F14, 749F16, 749F20, 750F10, 750F12, 750F14, 750F16, 750F20, 751F12, 751F14, 751F16, 751F20, 752F16

Pressure terminal connectors, angled-90 degrees, "L Series", Model(s) L6, L10, L16, L25, L35, L50, L70, L95, L120, L150, L185, L240, L300, L400, followed by a /1 or /2-digit number, and by suffix -90, may be followed by Suffix bk.

Pressure terminal connectors, fork type, "Q Series", Model(s) Nos. 1652C5, 1652C6, 1653C6, 1653C8

Pressure terminal connectors, fork type, "R Series", Model(s) 91C, 92C, 93C, 94C, 95C, 96C, or 97C, followed by a 1-digit number, may be followed by Suffix bk, or Pb.

Pressure terminal connectors, pin type, "Q Series", Model(s) Cat. Nos. ST1716, ST1717, ST1718, ST1719, ST1720, ST1721, ST1722

Pressure terminal connectors, splice, "F Series", Model(s) ", Cat. Nos. 722F, 723F, 724F, 725F, 726F, 727F, 728F, 729F, 730F, 731F

Pressure terminal connectors, straight, "F Series", Model(s) Cat. Nos. 702F5, 702F6, 702F8, 702F10, 702F12, 703F5, 703F6, 703F8, 703F10, 703F12, 704F5, 704F6, 704F8, 704F10, 704F12, 705F6, 705F8, 705F10, 705F12, 705F14, 706F6, 706F8, 706F10, 706F12, 706F14, 706F16, 707F8, 707F10, 707F12, 707F14, 707F16, 708F8, 708F10, 708F12, 708F14, 708F16, 709F10, 709F12, 709F14, 709F16, 709F20, 710F10, 710F12, 710F14, 710F16, 710F20, 711F12, 711F14, 711F16, 711F20, 712F12, 712F14, 712F16, 712F20

Pressure terminal connectors, straight, "L Series", Model(s) L0.75, L1.5, L2.5, L4, L6, L10, L16, L25, L35, L50, L70, L95, L120, L150, L185, L240, L300, L400, L500 or L630, followed by a 1 or 2-digit number, and by suffix MS, may be followed by Suffix bk.

Pressure terminal connectors, straight, "NDC Series", Model(s) NDC0.75, NDC1.5, NDC2.5, NDC4, NDC6, NDC10, NDC16, NDC25, NDC35, NDC50, NDC70, NDC95, NDC120, NDC150, NDC185, NDC240, NDC300, NDC400, NDC500 or NDC630, followed by a 1 or 2-digit number.

Pressure terminal connectors, straight, "Q Series", Model(s) Cat. Nos. 16525, 16526, 16528, 165210, 165212, 16535, 16536, 16538, 165310, 165312, 16545, 16546, 16548, 165410, 165412, 165416, 16556, 16558, 165510, 165512, 165516, 16566, 16568, 165610, 165612, 165616, 16576, 16578, 165710, 165712, 165716, 16588, 165810, 165812, 165816, 16598, 165910, 165912, 165916, 166010, 166012, 166016, 166112, 166116, 166212, 166216

Pressure terminal connectors, straight, "R Series", Model(s) 1R, 2R, 3R, 4R, 5R, 6R, 7R, 8R, 9R, 10R, 11R, 12R, 13R, 14R, or 15R, followed by /1 or 2-digit number, may be followed by Suffix bk, or Pb.

91R, 92R followed by /3, /4, /5, or /6 may be followed by Suffix bk, or Pb.

93R, 94R, 95R followed by /3, /4, /5, /6 or /8 may be followed by Suffix bk, or Pb.

Last Updated on 2014-02-18

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".